

CODE	Description	Qty	Unit
	Mild steel reinforcement bars, twisted (deformed) and commercial grade m, yield strength 60 ksi, length 6m, Nominal size :		-
10-01-60001	25 mm diameter	355	MT
10-01-60002	20 mm diameter	280	MT
10-01-60003	16 mm diameter	750	MT
10-01-60004	12 mm diameter	2150	MT
10-01-60005	10 mm diameter	1100	MT
10-01-60006	Steel plate (flat) Gauge 18, size 4' x 8'	40	MT
10-01-60007	Standard mild steel, T profile, 6m length, 25x25x3 mm	4	MT
10-01-60008	Standard mild steel, Z profile, 6m length, 25x25x3 mm	10	MT
10-01-60009	Standard mild square steel bars 10x10 mm, 6m length	10	MT
10-01-60010	Standard mild steel square pipes (hollow) 40x40x3 mm, 6m length	10	MT
	Ductile iron pipe with rubber gasket joints (tyton joints) 6m length & PN20/PN25. Nominal diameter:		-
10-01-60011	150 mm diameter	8100	Meter
10-01-60012	100 mm diameter	6000	Meter
	Equal elbow for ductile pipes with rubber gasket tyton joint 90 degrees FxF, PN20/ PN25, nominal diameter:		-
10-01-60013	150 mm diameter	50	No.
10-01-60014	100 mm diameter	25	No.
	Equal elbow for ductile pipes with rubber gasket tyton joint 45 degrees FxF, PN20/ PN25, nominal diameter:	-	-
10-01-60015	150 mm diameter	15	No.
10-01-60016	100 mm diameter	15	No.
	Equal tee for ductile pipes with rubber gasket tyton joint FxFxF, PN20/25. Nominal diameter:	-	-
10-01-60017	150 mm diameter	15	No.
10-01-60018	100 mm diameter	15	No.
	Parallel reducer for ductile pipes with rubber gasket tyton joint FxFxF, PN20/PN25. Nominal diameter:	-	-
10-01-60019	150 x 100 mm diameter	40	No.
	Equal sockets for ductile pipes with rubber gasket tyton joint FxF, PN20/PN25. Nominal diameter:	-	-
10-01-60020	150 mm diameter	15	No.
10-01-60021	100 mm diameter	7	No.
	Standard sockets & spigot for ductile pipes with rubber gasket tyton joint FxM, PN20/PN25. Nominal diameter:	-	-
10-01-60022	150 mm diameter	25	No.
10-01-60023	100 mm diameter	15	No.
	Flexible coupling to connect two spigot ended ductile iron pipes, ISO flanges, Nominal diameter:		

CODE	Description	Qty	Unit
10-01-60024	150 mm diameter	40	No.
10-01-60025	100 mm diameter	20	No.
	Bolted flanged spigot joints for ductile pipes with bolts, nuts & gaskets PN20/PN25, ISO flanges. Nominal diameter:	-	-
10-01-60026	150 mm diameter	15	No.
10-01-60027	100 mm diameter	7	No.
	Flanged gate valve for ductile pipes with bolts & nuts and gasket PN20/PN25, ISO flanges. Nominal diameter:	-	-
10-01-60028	150 mm diameter	10	No.
10-01-60029	100 mm diameter	7	No.
	Flanged non return valves for ductile pipes with bolts & nuts and gasket, PN20/PN25, ISO flange. Nominal diameter:	-	-
10-01-60030	150 mm diameter	6	No.
10-01-60031	100 mm diameter	4	No.
	Mild steel welded hot dip galvanised iron pipe for drinking water supply conforming ISO R65-1981, medium series standards. Threaded BS21 (ISO R7) with standard socket at one end & plastic heavy gauge cap protection at the other end, 6 m length, Nominal diameter:	-	-
10-01-60032	100 mm. diameter (3in.)	10200	m
10-01-60033	75 mm. diameter (2 1/2in.)	10200	m
10-01-60034	50mm. diameter (2in.)	8100	m
	Submersible pump with direct coupled electrical motor, 15 kW, 20 hp with non-return valve, control panel complete set. 170 m three core cable, tail cable and cable termination, 380 V, 50 Hz, 3 phase, (Grundfos).	-	-
10-01-60035	SP-8A-18	2	No
10-01-60036	SP-8A-25	1	No
10-01-60037	SP-16-12	2	No
10-01-60038	SP-16-20	2	No
10-01-60039	SP-27-16	4	No
10-01-60040	SP-46-8	1	No
10-01-60041	SP-46-14	1	No
10-01-60042	SP-27-36	1	No
10-01-60043	Turbine submersible pump with vertical motor + gear box+discharge+ pipes, colman bearing with shaft : 15m3/hr, H=160 m, pepes 3 ml., Dia 3" or 4" with shaft for depth of 160 m. (Grundfos SP-16-18)	2	No